

Market Information

04.01.2011

New Coiled Cable for the Trailer Lighting

In our current product range we have both ABS and EBS coiled cables and we are happy extend our offering with the introduction of the ISO 12098-compliant, 15 pin colled cable for the lighting system.

Like other WABCO cables, this cable has been subjected to around two dozen different tests, such as flexing cycle testing, vibration, torsion, cyclic strain and temperature change testing.

These tests are necessary to ensure the high quality required by products of our brand and it is also the only way to guarantee that we meet the ISO 12098 standard and distinguish ourselves from many other competitive products.

In a <u>TÜV certificate</u> WABCO additionally received the proof of the compliance to the ADR requirements.



Water can run down cables

Please note that cables can transfer water, Valuable Trailer EBS E Modulators have failed because supposedly economical / cheaper cables of low quality were used. Leaks in these cables allow water to run along them to the Trailer EBS E Modulators.

Don't save on the wrong end, Rely on well-known WABCO quality.

Overview of Trailer Connection Products		
Application	WABCO number	Description
Lighting ISO 12098	446 008 710 0	15 pin. Working length 3m. Coil diameter 60mm
EBS and ABS ISO 7638	446 008	Market information EBS Trailer - Coiled cable
Wendelflex	452 711	Market information WABCO Wendelflex
Premiumflex	452 713	Market information WABCO PremiumFlex