



- ① = Min. required torque 25 ± 3 Nm designed for M10 thread. Fastener selection and strength prove of this connection needs to be performed by customer.  
Customer is responsible to avoid damages at his trailer door. Customer should do his own screw calculation.
- ② = Secure by Loxeal 55-03 glue.

BEFORE MOUNTING, PLEASE CHECK THE OPTIFLOW™ TAIL INSTALLATION MANUAL FOR FURTHER DETAILS  
CONSULT COMPLETE ASSEMBLY INSTALLATION DRAWING FOR DETAILED HOLE POSITIONING

General Specifications JED-334-1, Size ISO 14405 LP				Copyright WABCO®		<b>WABCO</b>																			
Further Technical Data:				Date		Signature																			
Doc. Codes		Sheets To		Drawn		EU50 TP reefer R																			
General Tolerances JED-2b1				2015-03-27		Evektor																			
<div>Range of Nominal Dimensions (mm)</div> <table><tr><td>≤ 50</td><td>&gt; 50 ≤ 100</td><td>&gt; 100 ≤ 180</td><td>&gt; 180 ≤ 400</td></tr><tr><td>0,5</td><td>1,0</td><td>1,5</td><td>2,0</td></tr><tr><td>1,0</td><td>2,0</td><td>3,0</td><td>4,0</td></tr><tr><td>Coarse</td><td>2,0</td><td>3,5</td><td>5,0</td></tr></table>				≤ 50	> 50 ≤ 100	> 100 ≤ 180	> 180 ≤ 400	0,5	1,0	1,5	2,0	1,0	2,0	3,0	4,0	Coarse	2,0	3,5	5,0	Checked		Manufacturer codes			
				≤ 50	> 50 ≤ 100	> 100 ≤ 180	> 180 ≤ 400																		
				0,5	1,0	1,5	2,0																		
				1,0	2,0	3,0	4,0																		
Coarse	2,0	3,5	5,0																						
				2015-07-15		032_03_SV363																			
				Expert																					
				L. Ramirez																					
Class 1)				Mass		Material No.		Date of first issue																	
Fine				Scale		1812300030		Doc.Code Language Sheet																	
Medium				7,4 kg 1:2				005 EN 1/1																	
Coarse				Size CAD System																					
Tapped Holes acc. -				A1				Replacement for																	
1) Tolerance Class Applied Crossmarked				CATIA																					
1 1				1 1		100mm																			