







A											IDENTIFICATION		BACK FLOW LIMITING VALVE: RUECKSTROMBEGR VENTIL: <i>Δp</i> (bar)		BODY GEHAEUSE BOITIER CORPO		I	II	III	IV	HEATING HEIZUNG CHAUFFAGE RISCALDAMENTO		DRYER RESERVOIR TROCKENMITTELBEHAELTER CARTOUCHE DU DESSICATEUR CARTUCCIA ESSICCANTE		THREAD IN PORT GEWINDE IN ANSCHLUSS: FILETAGE EN ORIFICE FILETTO IN ORIFIZIO				(kg) MASS MASSE MASSA
											WABCO	CUSTOMERS NO KUNDEN-NR. NO CLIENT CLIENTE													1	2 1	4	b	
											432 413 007 R		0.7 +0.05/-0.1		432 410 575 2		×	×		894 260 046 2 12V==100W		432 420 220 2		1/2-14 NPTF		1/2-14 NPTF	1/4-18 NPTF	1/2-13 UNC 2B	4.74



THERMAL RANGE OF CONTINUOUS APPLICATION:
THERMISCHER DAUERANWENDUNGSBEREICH
PLAGE DE TEMPERATURE EN UTILISATION CONTINUE
COMPO DI APPLICAZIONE CONTINUA

RESISTANCE TO HEAT
WAERMEBESTAENDIGKEIT
RESISTANCE A LA CHALEUR
RESISTANZA AL CALORE

MEDIUM COMPRESSED AIR
MEDIUM DRUCKLUFT
FLUIDE AIR COMPRI ME
FLUIDO ARIA COMPRESSA

WORKING PRESSURE
BETRIEBSDRUCK
PRESSION DE SERVICE
PRESSIONE D' ESERCIZIO

INSTALLATION POSITION AS DRAWN
EINBAULAGE WIE GEZEICHNET
POSITION D' INSTALLATION SUIVANT DESSIN
POSIZIONE DI MONTAGGIO COME DISEGNATO

TORQUE FOR CONNECTIONS:
ANZUGSMOMENT FUER EINSCHRAUBSTUIZEN
COUPLE DE SERRAGE DES RACCORDS
COPPIA DI SERRAGGIO DEI RACCORDI

IN CASE OF GREASED THREAD
BEI GEFETTETEM GEWINDE
EN CAS DE FILETAGE GRAISSE
IN CASO DI FILETTATURA INGRASSATA

COMBINED UNLOADER:
DRUCKREGLER
REGULATEUR DE PRESS
GRUPPO DI REGOLAZIONE

HEATING
HEIZUNG
CHAUFFAGE
RISCALDAMENTO

CUT-IN TEMPERATURE
EINSCHALT-TEMPERATUR
TEMPERATURE DE FERMETURE
TEMPERATURA DI CHIUSURA

BATTERY VOLTAGE:
BATTERIESPANNUNG
TENSION DE BATTERIE
TENSIONE DI BATTERIA

POWER
LEISTUNG
PUISSANCE
POTENZA

SAFETY PRESSURE OF THE IDLE CONTROL VALVE AT
SICHERHEITSDRUCK DES LEERLAUFVENTILES BEI V

CUT OUT PRESSURE
ABSCHALTDRUCK
PRESSION DE DECL
PRESSIONE D' APERTURA

CUT-OFF TEMPERATURE
AUSSCHALT-TEMPERATUR
TEMPERATURE DE MISE
TEMPERATURA DI APERTURA

WITH
AVEC
CON

SAFETY VALVE
SICHERHEITSVENTIL
SOUPAPE DE SECURITE
VALVOLA DI SICUREZZA

OPENING PRESSURE
OEFFNUNGSDRUCK
PRESSION D' OUVERTURE
PRESSIONE DI APERTURA

APPLIED ACROSS THE HEATER CONTACTS
DIREKT AN DEN HEIZUNGSKONTAKTEN
APPLIQUEE SUR LES CONTACTS DE CHAUFFAGE
APPLICATA SULLE CONTATTI DI RISCALDAMENTO

- FROM THE COMPRESSOR
VOM LUFTPRESSER
PROVENANT DU COMPRESSEUR
PROVENIENTE DEL COMPRESSORE
- TO THE RESERVOIRS
ZU DEN LUFTBEHAELTERN
AUX RESERVOIR
AL SERBATOII PER
- EXHAUST FOR COMPRESSED AIR
ENTLUEFTUNG FUER DRUCKLUFT
ECHAPPEMENT POUR AIR COMPRI ME
SCARIC PER ARIA COMPRESSA
- EXHAUST OF THE SAFETY VALVE
ENTLUEFTUNG DES SICHERHEITSVENTILES
ECHAPPEMENT DE LA SOUPAPE DE SECURITE
SCARICO DELLA VALVOLA DI SICUREZZA
- CONTROL PORT
STEUERANSCHLUSS
ORIFICE DE COMMANDE
ORIFIZIO DI COMANDO

General Specification: JED-534-1 - Size: ISO 14405 LPT				Copyright: WABCO®				WABCO			
Further Technical Data:				Date: 2015-04-22				AIR DRYER LUFTTROCKNER DESSICATEUR D'AIR ESSICCATORE D'ARIA			
Doc. Code: 030				Sheet: 1 To: 1				Date of first issue: 063 ML 1/1			
General Tolerances: ISO-201				2015-04-22				Revision: 2010			
Range of Nominal Dimensions (± mm)				Corcoran				Replacement for:			
Class II ± 50 ± 80 ± 100 ± 120 ± 150 ± 200				Corcoran							
Fine: 0.5 1.0 1.5 2.0				Corcoran							
Medium: 1.0 2.0 3.0 4.0 5.0				Corcoran							
Coarse: 2.0 3.5 5.0 6.5				Corcoran							
Tapped Holes acc.				A O							
Tolerances Class: Applied: Unspecified				CREO							