
	MATERIAL MATERIAL MATIERE MATERIALE		SURFACE PROTECTION OBERFLAECHENSCHUTZ PROTECTION SUPERFICIELLE PROTEZIONE SUPERFICIALE	
I	PBT GF 30 SEALING JOINT DICHTUNG GUARNIZIONE SILICON SEALING	JED-352-10 JED-675-6		
II	CuNi3Si1Mg R620	JED-826-2	Sn	1.5 - 3µm
III	Al CuBiPb			
IV	PA 66 GF35	JED-359-9		
V	PA 6 GF 15	JED-668-1		


SPECIAL CHARACTERISTICS ACC. TO ZFN 1204				
CHARACTERISTIC CLASS	C	S	PTC	P
ASSIGNED TOTAL NUMBER	0	1	0	0
HIGHEST NUMBER	0	1	0	0

THIS DEVICE CONTAINS A 434 MHz RADIO TRANSMITTER
AND RECEIVER AND MATCHING INTEGRATED PCB ANTENNA:
IT MUST NOT BE MOUNTED DIRECTLY ON A METAL SURFACE:
A CUT-OUT AREA (MIN.65mmx145mm,CENTERED ON ECU)
IN THE MOUNTING BRACKET IS RECOMMENDED


PROPOSED MOUNTING BRACKET
WABCO PARTNO. 446 220 000 4 OR SIMILAR




1:5




TORQUE:
ANZUGSMOMENT: 15 Nm ± 10%
COUPLE DE SERRAGE:
COPPIA DI SERRAGGIO:





CONNECTOR ACC. TO INTERFACE DRAWING: 858 000 854 4 REV.D1
TYCO DESIGN ACC.TO TYCO DRAWING C-114-18740-1 CODING: A
STECKER GEMAESS SCHNITTSTELLENZEICHNUNG: 858 000 854 4 REV.D1
TYCO AUSFUEHRUNG GEMAESS TYCO ZEICHNUNG C-114-18740-1 KODIERUNG: A
CONNECTEUR SUIVANT DESSIN D'INTERFACE: 858 000 854 4 REV.D1
TYCO REAUSATION SUIVANT TYCO DESSIN: C-114-18740-1 CODIFICATION: A
CONNETTORE SECONDO DISEGNO DI INTERFACCIA: 858 000 854 4 REV.D1
TYCO SOLUZIONE SECONDO TYCO DISEGNO: C-114-18740-1 ESPRESSIONE IN CODICE: A


1:5



INSTALLATION POSITION:
EINBAULAGE:
POSITION D'INSTALLATION:
POSIZIONE DI MONTAGGIO:

MOUNTING DIRECTION OPTIONAL

1:5



Ⓔ S 1 ① WABCO LABEL. CONTENTS SEE DOCUMENT 'LABELING INFORMATION'
TYPENSCHILD. ANGABEN SIEHE DOKUMENT 'LABELING INFORMATION'
PLAQUE DE FIRME. INDICATIONS VOIR DOCUMEN 'LABELING INFORMATION'
TARGHETTA. INDICAZIONI VEDERE DOCUMENTO 'LABELING INFORMATION'
(446 220 110 0 DOC. CODE 922)

VOLTAGE:
SPANNUNG:
VOLTAGE: 8V ... 32V (TYP. +12V, +24V) DC
VOLTAGGIO:

DEGREE OF PROTECTION PROVIDED BY ENCLOSURE:
COMPLETE DEVICE WITH MOUNTED CONNECTOR SOCKET:
SCHUTZART:
KOMPLETTES GERAET MIT MONTIERTER STECKVERBINDUNG:
MODE DE PROTECTION:
APPAREIL COMPLET AVEC L'ACCOUPLEMENT:
MODO DI PROTEZIONE:
APPARECCHIO COMPLETO CON ACCOPPIAMENTO MONTATO:

THERMAL RANGE OF APPLICATION:
THERMISCHER ANWENDUNGSBEREICH: -40°C...+85°C
GAMME D'APPLICATION THERMIQUE
CAMPO TERMICO D'APPLICAZIONE:

NON-OPERATING TEMPERATURE
TEMPERATUR AUßER BETRIEB -40°C...+85°C
TEMPÉRATURE HORS FONCTIONNEMENT
TEMPERATURA FUORI ESERCIZIO

DEVICE SHALL BE OPENED BY MANUFACTURER ONLY
GERAET DARF NUR VOM HERSTELLER GEOEFFNET WERDEN
L'APPAREIL NE DOIT ETRE OUVERT QUE PAR LE FABRICANT
IL APPARECCHIO DEVE ESSERE APERTO PER IL PRODUTTORE SOLAMENTE

NOTE: PLEASE DO NOT TOUCH THE MALE MULTIPOINT CONNECTOR CONTACTS
HINWEIS: KONTAKTSTIFTE BITTE NICHT BERUEHREN
NOTE: S.V.P. NE PAS TOUCHER LES CONTACTS DU CONNECTEUR MALE MULTIBROCHE
NOTA: PER FAVORE NON TOCCARE I CONTATTI DEL CONNETTORE MASCHIO MULTIPLO

INSTALLATION POSITION TO BE DEFINED ACCORDING TO VEHICLE TYPE
FAHRZEUGANBAUORT FAHRZEUGTYPSPEZIFISCH FESTZULEGEN
POSITION D'INSTALLATION DOIT ETRE DEFINIE SUIVANT TYPE DE VEHICULE
POSITIONE DI MONTAGGIO DEVE ESSERE DETERMINATA SECONDO TIPO VEICOLO

FURTHER TECHNICAL DATA SEE PRODUCT SPECIFICATION (DOC. CODE 035)
WEITERE TECHNISCHE DATEN SIEHE PRODUKTSPEZIFIKATION
POUR AUTRES DONNEES TECHNIQUES VOIR SPECIFICATION DU PRODUIT
PER ULTERIORI DATI TECNICI VEDERE SPECIFICA DI PRODOTTO

PORT ANSCHLUSS	PORT ATTACCO	FUNCTION FUNKTION	FUNCTION FUNZIONE
1		CAN LOW IN/OUT CAN NIEDRIG IN/OUT	CAN FAIBLE IN/OUT CAN BASSO IN/OUT
2		CAN HIGHT IN/OUT CAN HOCH IN/OUT	CAN HAUPT IN/OUT CAN ELEVATO IN/OUT
3		LAMP OUTPUT (1) OR DIGITAL INPUT(1)* LAMPENAUSGANG (1) ODER DIGITALEINGANG (1)*	PUISSANCE DE LA LAMPE (1) OU ENTREE NUMERIQUE (1)* POTENZA DELLA LAMPADA (1) O INGRESSO DIGITALE (1)*
4		LAMP OUTPUT (2) OR DIGITAL INPUT(2)* LAMPENAUSGANG (2) ODER DIGITALEINGANG (2)*	PUISSANCE DE LA LAMPE (2) OU ENTREE NUMERIQUE (2)* POTENZA DELLA LAMPADA (2) O INGRESSO DIGITALE (2)*
5		CAN - GND CAN - GND	CAN - GND CAN - GND
6		BRAKE LIGHT (INPUT) BREMSLICHT (INPUT)	FEU D'ARRET (INPUT) SEMAFORO (INPUT)
7		OPERATING VOLTAGE (INPUT TYP +12V, +24V, TERMINAL 30) BETRIEBSSPANNUNG (INPUT TYP +12V, +24V, TERMINAL 30)	TENSION DE FONCTIONEMENT (INPUT TYP +12V, +24V, TERMINAL 30) TENSIONE DI FUNZIONAMENTO (INPUT TYP +12V, +24V TERMINAL 30)
8		VEHICLE GROUND (GND) FAHRZEUGMASSE (GND)	LA MASSE DU VEHICLE (GND) MASSA DEL VEICOLO (GND)

General Specification: ISO 8015, JED-334-1, Size ISO 14405 LP					
Further Technical Data:					
Doc. Code:			Sheet:		To
General Tolerances JED-261					
	Range of nominal dimensions in mm				
Class 1)	< 50	> 50 < 180	> 180 < 400	> 400	
Fine	±0.5	±1	±1.5	±2	±3°
Medium	±1	±2	±3	±4	
Coarse	±2	±3.5	±5	±6.5	
Tapped Holes acc.					
1) Tolerance Class Applied Crossmarked					

Copyright ZF

Date	Signature
Drawn 2026-09-16	Be□cz□cka
Checked 2026-09-18	von der Beeke

ECU-HW TPMS OPTITIRE

Dimensions in mm

Mass	Scale	Material No.	Date of first issue: 2015-10-13		
0.281 kg	1:1	446 220 110 0	Doc.Code	Language	Sheet
			005	ML	1/1
Size	CAD System	ECN-No. / Revision / Techn. Resp. / Replacement for			
A1	CREO	521226 / 3x / E / 6031			

100mm

Tous Communication ou reproduction de ce document, toute exploitation ou communication de son contenu sont interdites, sauf autorisation expresse. Tous droits de propriété industrielle réservés, notamment en matière de brevets, d'dessins et de modèles.
Non è permesso consegnare o terzi o riprodurre questo documento, né utilizzare il contenuto o renderlo comunque noto a terzi senza espressa autorizzazione scritta. Ogni diritto derivante da brevetti o modelli.
Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Geschmacksmustereintragung vorbehalten.
Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of patent or registration of a utility model or design. This document is the subject of copyright.