



5-CORE CABLE	:	} PVC	3x1.5mm ² ①
LEITUNG 5-ADIG	:		
CABLE A 5-CONDUCTEURS	:		
CAVO A 5-CONDUTTORI	:		
			2x4mm ²

THERMAL RANGE OF APPLICATION:
THERMISCHER ANWENDUNGSBEREICH: -40 °C....+80 °C
GAMME D'APPLICATION THERMIQUE:
CAMPO TERMICO D'APPLICAZIONE:

MOUNTED CABLE RESISTANT TO	:	}	AIR, WATER, MINERAL OIL, PETROL, DIESEL OIL, SALT SPRAY
MONTIERTES KABEL BESTÄNDIG GEGEN:	:		LUFT, WASSER, MINERALÖL, BENZIN, DIESELÖL, SALZSPRÜHNEBEL
CABLE MONTÉ RESISTANT A	:		AIR, EAU, HUILE MINÉRALE, ESSENCE, GASOIL, BROUILLARD SALIN
CAVO MONTATO RESISTENTE A	:		AIRIA, ACQUA, OIL MINERALI E BENZINA, GASOLI, NEBBIA SALINA

DEGREE OF PROTECTION (IN CONNECTION WITH PLUG) :
SCHUTZART (IN VERBINDUNG MIT STECKER) :
DEGRE DE PROTECTION (DANS CONNECTION AVEC FICHE):
GRADO DI PROTEZIONE (IN RELAZIONE CON SPINA) : } IP 54
ISO 20653(en)

INSTALLATION INSTRUCTIONS FOR CABLES TO BE OBSERVED. SEE DOCUMENT :
EINBAUHNWEISE FÜR KABEL SIND ZU BEACHTEN. SIEHE DOKUMENT :
IL FAUT OBSERVER LES INDICATIONS POUR L'INSTALLATION DES CABLES. VOIR DOCUMENT :
SONO DA OSSERVARE GLI INDICAZIONI DI MONTAGGIO DEI CAVI. VEDERE DOCUMENTO :

[illegible]