

INTERFACE SPECIFICATION:
AUSFUEHRUNGSVORSCHRIFT: 858 000 866 4
DESCRIPTION D'INTERFACE:
DESCRIZIONE DI INTERFACCIA:

Diagram of a 16-pin D-sub connector. The pins are numbered 1 to 8 on both sides. The pin configurations are as follows:

Pin Number	Color	Wire Gauge
1	PK	1.0mm ²
2	WH/GN	0.35mm ²
3	WH/BN	0.35mm ²
4	WH	1.0mm ²
5	BK	0.5mm ²
6	YE/BK	0.5mm ²
7	YE/BN	0.5mm ²
8	BN	1.0mm ²

Pins 9 through 16 are not labeled.

CODE OF LENGTH LAENGENCODIERUNG CODE DE LA LONGUEUR CODICE DEL LUNGHEZZA	
PART NO TEILE NR. NO DE PIECE CODICE	L[m] 449 303 ☐ ☐ ☐ 0
EXAMPLE BEISPIEL EXEMPLE ESEMPIO	L = 1.5m 449 303 015 0
MIN/MAX LENGTH MIN/MAX LAENGE MIN/MAX LONGUEUR MIN/MAX LUNGHEZZA	L _{min} = 0.2m L _{max} = 10m
TOLERANCES TOLERANZEN TOLERANCES TOLERANZA	L ≤ 10m ±0.050m L > 10m ±0.075m

MOUNTED CABLE RESISTANT TO : AIR, WATER, MINERAL OIL, DIESEL OIL, SALT SPRAY
 MONTIERTES KABEL BESTÄNDIG GEGEN: LUFT, WASSER, MINERALÖL, DIESELÖL, SALZSPRÜHNEBEL
 CABLE MONTÉ RESISTANT A : AIR, EAU, HUILE MINÉRALE, GAZOIL, BROUILLARD SALIN
 CAVO MONTATO RESISTENTE A : ARIA, ACQUA, OLIO MINERALE, GASOLIO, NEBBIA SALINA

General Specification: JED-334-O **					Copyright WABCO®		WABCO				
Further Technical Data:					Date _____ Signature _____		CABLE WITH SOCKET KABEL MIT GERÄTESTECKDOSE CABLE AVEC PRISE DE COURANT CAVO CON PRESA DI CORRENTE				
Doc. Code:		Sheet: _____ To _____			2010-12-17 Drawn _____ Checked _____						
General Tolerances JED-261					2010-07-15 Expert _____ Nebner _____						
Range of Nominal Dimensions (± mm)											
Class 1)	≤ 50	> 50 ≤ 180	> 180 ≤ 400	> 400	±3°	Mass _____ Scale _____		Material No. _____		Date of first issue _____	
Fine	0,5	1,0	1,5	2,0		1:1		449 303 000 0		053 ML 1/1	
Medium	1,0	2,0	3,0	4,0		/ kg CAD System _____					
Coarse	2,0	3,5	5,0	6,5							
Tapped Holes acc. _____					A 1 Pro/E 		ECN-No. _____ Revision _____ Techn. Resp. _____		Replacement for _____		
1) Tolerance Class Applied Crossmarked											