

INSTALLATION INSTRUCTIONS TO BE OBSERVED:
 INSTALLATIONSHINWEIS BEACHTEN: 449 000 000 0
 INDICATION POUR L'INSTALLATION À OBSERVER: (DOC. CODE 011)
 OSSERVARE INDICAZIONE DI MONTAGGIO:

THERMAL RANGE OF APPLICATION :
 THERMISCHER ANWENDUNGSBEREICH: -40 °C...+65 °C
 GAMME D'APPLICATION THERMIQUE:
 CAMPO TERMICO D'APPLICAZIONE :



MOUNTED CABLE RESISTANT TO : AIR, WATER, MINERAL OIL, DIESELOIL, SALTSpray
 MONTIERTES KABEL BESTAENDIG GEGEN: LUFT, WASSER, MINERALOEL, DIESELOEL, SALZSPRUEHNEBEL
 CABLE MONTÉ RESISTANT A : AIR,EAU, HUILE MINERALE, GASOIL, BROUILLARD SALIN
 CAVO MONTATO RESISTENTE A : ARIA, AQUA, OLIO MINERALE, GASOLIO, NEBBIA SALINA

DEGREE OF PROTECTION (IN CONNECTION WITH PLUG) :
 SCHUTZART (IN VERBINDUNG MIT STECKER) : A: IP 6K6K, IP 6K9K
 DEGRE DE PROTECTION (DANS CONNECTION AVEC FICHE): C: IP 54
 GRADO DI PROTEZIONE (IN RELAZIONE CON SPINA) : ISO 20653

8-CORE CABLE:
 LEITUNG 8-ADRIG:
 CABLE A 8 CONDUCTEURS: 3x1mm² + 3x0.5mm² + 1x (2x0.35mm²)
 CAVO A 8 CONDUTTORI:

* SURFACE PROTECTION :
 OBERFLAECHENSCHUTZ : Sn
 PROTECTION DE SURFACE:
 PROTEZIONE SUPERFICI :


IDENTIFICATION OF COUNTRY OR ORIGIN
 KENNZEICHNUNG WARENURSPRUNGSLAND
 IDENTIFICATION DA PAYS D'ORIGINE
 IDENTIFICAZIONE DEL PAESE D'ORIGINE



CABLE SEAL AGAINST INGRESS WATER REQUIRED
 KABELDICHTUNG GEGEN EINDRINGEN VON WASSER ERFORDERLICH
 PRESSE-ETOUPE DE CABLE NECESSAIRE POUR PROTECTION CONTRE L'EAU
 E NECESSARIO SERRACAVO PER PROTEZIONE DALL'INGRESSO DI ACQUA

CHAMBER IN: KAMMER IN: CHAMBRE EN: CAMERA IN:	CABLE KABEL CABLE CAVO	WIRE COLOUR ADER FARBE FIL COLEURE FILO COLORE
1	1.0mm ²	PINK PINK ROSE ROSA
2	0.35mm ²	WHITE/GREEN WEISS/GRÜN BLANC/VERT BLANCO/VERDE
3	0.35mm ²	WHITE/BROWN WEISS/BRAUN BLANC/BRUN BLANCO/BRUNO
4	1.0mm ²	WHITE WEISS BLANC BLANCO
5	0.5mm ²	BLACK SCHWARZ NOIR NERO
6	0.5mm ²	YELLOW/BLACK GELB/SCHWARZ JAUNE/NOIR GIALL/NERO
7	0.5mm ²	YELLOW/BROWN GELB/BRAUN JAUNE/BRUN GIALL/BRUNO
8	1.0mm ²	BROWN BRAUN BRUN BRUNO

CODE OF LENGTH LAENGCODIERUNG CODE DE LA LONGUEUR CODICE DEL LUNGHEZZA	PART NO. TEILE NR. NO DE PIECE CODICE	L[m]
	449 908	□ □ □ 0
EXAMPLE BEISPIEL EXEMPLE ESEMPIO		L = <u>6</u> m 449 908 060 0
MIN/MAX LENGTH MIN/MAX LAENGE MIN/MAX LONGUEUR MIN/MAX LUNGHEZZA		L _{min} = 0.2m L _{max} = 10m
TOLERANCES TOLERANZEN TOLERANCES TOLERANZA		L ≤ 10m ±0.050m L > 10m ±0.075m



** DIN 16901-150

General Specifications: JED-334-0 **		Copyright WABCO®		WABCO	
Further Technical Data:		Date:	Signature:	CABLE WITH SOCKET	
Doc. Code:	Sheet: To:	2010-07-12	Nieber	KABEL MIT GERAETESTECKDOSE	
General Tolerances JED-261		2010-07-15	Hoefler	CABLE AVEC PRISE DE COURANT	
Range of Nominal Dimensions (± mm)		Expert		CAVO CON PRESA DI CORRENTE	
Class	1) ≤ 50	> 50 ≤ 180	> 180 ≤ 400	Material No. 449 908 000 0	
Fine	0.5	1.0	1.5	Date of first issue: 2010-07-15	
Medium	1.0	2.0	3.0	Doc. Code: 053	
Coarse	2.0	3.5	5.0	Language: ML	
Tapped Holes acc.:		A 1		Sheet: 1/1	
Tolerance Class Applied Crossmarked		Pro/E		Revision: 6172_EM	
		ECN No.:		Tech. Resp.:	
		-		6172_EM	
		-		Replacement for:	