



SYMBOL SYMBOL SYMBOLE SIMBOLO	DIN ISO 1219	
WORKING POSITION EINBAULAGE POSITION DE FONCTIONNEMENT POSIZIONE DI FUNZIONAMENTO	UNIMPORTANT BELIEBIG INDIFFERENTE INDIFFERENTE	
WORKING MEDIUM ARBEITSMEDIUM FLUIDE D'UTILISATION FLUIDO DI ESERCIZIO	COMPRESSED AIR DRUCKLUFT AIR COMPRIE ARIA COMPRESSA	
AMBIENT MEDIUM UMGEBUNGSMEDIUM FLUIDE AMBIANT FLUIDO AMBIENTE	AIR (CONTAINING WATER DUST AND OIL) LUFT (WASSER-, STAUB- UND OELHALTIG) AIR (HUMIDE, HUILEUX, POUSSIEREUX) ARIA (ACQUA, POLVERE ED OLIO INQUINATO)	
WORKING TEMPERATURE THERMISCHER ARBEITSBEREICH TEMPERATURE DE FONCTIONNEMENT TEMPERATURA DI UTILIZZAZIONE	-40°+80°C	
MAX INLET PRESSURE MAX BETRIEDSDRUCK PRESSION D'ALIMENTATION MAXI PRESSIONE MASSIMA D'ALIMENTAZIONE	8.5 BAR	

ACCORDING TO JED-152  
 \* THREAD LENGTH MIN. = 13MM  
 \* THREAD LENGTH NOT VALID  
 WITH JED-152 BUT APPROVED

General Specification: JED-334-0		Copyright WABCO®		<b>WABCO</b>	
Further Technical Data: PS 952 200 000 0		Date:	Signature:	HOUSE COUPLING	
Doc. Code:	Sheet: To	2012-05-25	CEPENDA	KUPPLUNGDKOPF	
General Tolerances JED-261		2012-05-25	HLADIK	TESTA D'ACCOMPANIMENTO	
Range of Nominal Dimensions ( ± mm)		Expert		TETE D'ACCOUPEMENT	
Class 1)	< 50 > 50 > 180 > 180 > 400 > 400	CEPENDA			
Fine	0.5 1.0 1.5 2.0	Mass	Scale	Material No.	
Medium X	1.0 2.0 3.0 4.0	0.245	1:1	452 300 031 0	
Coarse	2.0 3.5 5.0 6.5	Size	CAD System	Date of first issue: 2012-05-25	
Tapped Holes acc. JED-152		A 2	Pro/E	Doc. Code Language Sheet	
1) Tolerance Class Applied Crossmarked				005 ML 1/1	
		ECON-No. Revision Techn. Resp.		Replacement for	
		157896 1 K 5710			

100mm