WABCO

TECHNICAL DATA

MEDIUM .....: MINERAL OIL, 10cSt UP TO 3000 cSt

RANGE OF WORKING PRESSURE .....: P_{abs} 0,2 UP TO 170 bar

OPENING PRESSURE IN THE PORTS A AND B: P_e 0 UP TO 0,1 bar

TEMPERATURE OF MEDIUM .....: -20°C UP TO +80°C

AMBIANT TEMPERATURE (ACTUATED).....: -20°C UP TO +80°C

AMBIANT TEMPERATURE (NOT ACTUATED)...: -40°C UP TO +120°C max. 1 h

PAINTING.....: BLACK SYNTHETIC RESIN VARNISH RAL 9005
PORTS AND HOLES FREE OF PAINT

STOP FOR THE OPERATOR VIA PISTON IN THE VALVE. VALVE CLEAN AND FREE OF BURRS.

MEDIUM.....: MINERALOEL; 10 cSt BIS 3000 cSt

BETRIEBSDRUCKBEREICH .....: P_{abs} 0,2 BIS 170 bar

OEFFNUNGSDRUCK IN DEN ANSCHLUESSEN
A UND B .....: P_e 0 BIS 0,1 bar

DRUCKMITTELTEMPERATUR.....: -20°C BIS +80°C

UMGEBUNGSTEMPERATUR (BETAETIGT).....: -20°C BIS +80°C

UMGEBUNGSTEMPERATUR (UNBETAETIGT)....: -40°C BIS +120°C max. 1 h

FARBANSTRICH .....: KUNSTHARZ DECKLACK SCHWARZ RAL 9005
ANSCHLUESSE UND BOHRUNGEN FARBFEI

ANSCHLAG DER BETAETIGUNG UEBER DEN KOLBEN IM VENTIL. VENTIL SCHMUTZ- UND GRATFREI.

Tous droits de propriété industrielle réservés. Riservati tutti i diritti in caso di concessione di brevetti o di registrazione di un modello di utilita.
All rights are reserved in the event of the grant of a patent or the registration of a utility model or design. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.