

	MEDIUM PNEUMATIC PART:	AIR
	WORKING PRESSURE:	P1/43 max. = 8.5 bar
	TEMPORARILY:	P1/43 max. = 10 bar
	MEDIUM HYDRAULIC PART:	MINERAL OIL
	WORKING PRESSURE:	P44 max.= 40 bar P41/42 max.= 100 bar
	TEMPORARILY:	P44 max. = 130 bar P41/42 max. = 120 bar
	HYDRAULIC WORKING VOLUME:	P41 ≤ 1.0 cm ³ P42 ≤ 1.0 cm ³ p44:1.5cm ³
	RESIDUAL PRESSURE IN THE HYDRAULIC SYSTEM:	P41 ≤ 0.1 bar P42 ≤ 0.1 bar
	THERMAL RANGE:	-40°C...+80°C
	TEMPORARILY:	UNPRESSURIZED th +110°C
①	CONTACT SURFACE	-
②	MIN.LENGTH OF HOSE: 200 mm	-
③	COVER WHEN PAINTING ON THE VEHICLE	-
④	CUSTOMER PART FOR MOUNTING OPTION 1	-
⑤	CUSTOMER PART FOR MOUNTING OPTION 2	-
⑥	MINIMUM THREAD ENGAGEMENT 2 x d	-
⑦	PROTECTING PLUG	-

Nominal Diameters			
Breakaway module status	From Part	To Part	Nominal diameter
Open	P1	P21/22	Ø 6mm
Closed	P1	P21	≥ Ø 1.5mm
n/o	P22	P3	Ø 10mm

