







MARKED WITH RED PAINT
MIT ROTEM LACK GEKENNZEICHNET
MARQUE AVEC VERNIS ROUGE
MARCARE CON VERNICE ROSSA


ACCORDING
NACH
SUIVANT
SECONDO




1	SUPPLY VORRAT ALIMENTATION ALIMENTAZIONE	2	OUTLET AUSGANG SORTIE USCITA	3	EXHAUST ENTLUEFTUNG ECHAPPEMENT SCARICO
41/42	HYDRAULIC CONTROL PRESSURE HYDRAULISCHER STEUERDRUCK PRESSION HYDRAULIQUE DE COMMANDE PRESSIONE IDRAULICO DI COMANDO				
	MEDIUM PNEUMATIC PART: MEDIUM PNEUMATIKTEIL: FLUIDE PARTIE PNEUMATIQUE: FLUIDO PARTE PNEUMATICA:		AIR LUFT AIR ARIA		
	WORKING PRESSURE: BETRIEBSDRUCK: PRESSION D'UTILISATION: PRESSIONE DI ESERCIZIO:	Pe max. = 7 bar	(TEMPORARILY: (KURZZEITIG: (DE COURTE DUREE: (BREVE TEMPO SOLO:		Pe max. = 10 bar)
	MEDIUM HYDRAULIC PART: MEDIUM HYDRAULIKTEIL: FLUIDE PARTIE HYDRAULIQUE: FLUIDO PARTIE IDRAULICA:		MINERAL OIL MINERALÖL HUILE MINERALE OLIO MINERALE		
	WORKING PRESSURE: BETRIEBSDRUCK: PRESSION D'UTILISATION: PRESSIONE DI ESERCIZIO:	Pe max. = 50 bar	(TEMPORARILY: (KURZZEITIG: (DE COURTE DUREE: (BREVE TEMPO SOLO:		Pe max. = 120 bar)
	HYDRAULIC WORKING VOLUME: HYDRAULISCHES ARBEITSVOLUMEN: VOLUME HYDRAULIQUE ABSORBE: VOLUME IDRAULICO ASSORBITO:	41 ≤ 1.0 cm ³ 42 ≤ 1.0 cm ³			
	RESIDUAL PRESSURE IN THE HYDRAULIC SYSTEM: RUECKHALTEDRUCK IM HYDRAULIKSYSTEM: PRESSION DE RETENUE AU SYSTEME HYDRAULIQUE: PRESSIONE DI RITENUTA NEL SISTEMA IDRAULICO:		p41 ≤ 0.1 bar p42 ≤ 0.1 bar		
	THERMAL RANGE OF APPLICATION: THERISCHER ANWENDUNGSBEREICH: GAMME D'APPLICATION THERMIQUE: CAMPO DI APPLICAZIONE TERMICA:	-40°C ... +80°C			
	INSTALLATION: EINBAULAGE: POSITION D'INSTALLATION: POSIZIONE DI MONTAGGIO:	VENTING SCREW MUST BE AT TOP ENTLUEFTUNGSSCHRAUBE MUSS NACH OBEN ZEIGEN BOUCHON DE PURGE DOIT ETRE MONTE EN HAUT LA VITE DI SCARICO DEVE ESSERE IN ALTO			



POSITION OF LEVER		I	II
HEBELSTELLUNG	p1	7 bar	7 bar
POSITION DU LEVIER	p2	0 bar	7 bar
POSIZIONE DELLA LEVA			



General Specifications: JED-334-O						Copyright WABCO®		WABCO TRAILER CONTROL VALVE ANHAENGER-STEUERVENTIL VALVE DE COMMANDE DE REM. VALVOLA DI COMANDO FR. RI.		
Further Technical Data:						Date	Drawn			Signature
Doc. Code:		Sheet:		To		2011-12-20	Chodorowski			Checked
General Tolerances JED-261						2011-12-20	Fuhrmann			Expert
Range of Nominal Dimensions (± mm)						Fabian				
Class	1)	≤ 50	> 50 ≤ 160	> 160 ≤ 400	> 400	±3°				
Fine		0.5	1.0	1.5	2.0					
Medium	X	1.0	2.0	3.0	4.0					
Coarse		2.0	3.5	5.0	6.5					
Tapped Holes acc.						Mass	Scale	Material No.	Date of first issue: 1993-09-20	
1) Tolerance Class Applied Crossmarked						0.932 KG	1:1	470 015 215 0	Doc. Code: Language: Steel	
						Size	CAD System			
						A 1	Pro/E			
						ECN-No.	Revision	Techn. Resp.	Replacement for	
						155688	2 D	5830	470 015 215 0 of 93-09-20	