



ID	TIGHTENING TORQUE	SIZE	REMARKS
①	200 ± 10 Nm +60°	ASR E20	PAD HOLD DOWN DEVICE ISO 4762 - M10x12 - 8.8
②	210 - 30 Nm	24	Operation cylinder M16x1.5 ISO 4762-M16x1.5x80-12.9
<C> ③	MAX. ROTARY OUTLINE		
<C> ④	MIN.FUNCTION STROKE		
⑤	FITTING DIMENSION OF THE DISC PERMISSIBLE		
⑥	BRAK DISC NEW 45-0.2. WEARABLE UP TO 37		
⑦	ASSEMBLY DIMENSION FOR BRAKE PADS		
⑧	PRODUCT IDENTIFICATION WABCO		
⑨	ENVELOPE CIRCLE CALIPER		
⑩	ENVELOPE CIRCLE CARRIER		
⑪	HEXAGON HEAD 8		
⑫	TRANSPORT LOCKS CAN BE USED OPTIONALLY		
⑬	CENTER LINE CYLINDER		
<C> ⑭	FORWARD DRIVE - ROTATION DIRECTION		
⑮	TRANSPORT TAPE REMOVED BEFORE MOUNTAGE		
⑯	BRAKE ACTUATOR - SEE PRODUCT SPECIFICATION MAX. ACTUATOR TYPE 22		
⑰	ANTI-CORROSION PROTECTION - SALT SPRAY TEST MIN. 96 HOURS		
⑱	DIMENSIONS WITHOUT TOLERANCE ARE GAUGE DIMENSIONS		

REMAN PN	CUSTOMER	IMAGE
640 222 003 R	IAM	AS DRAWN
640 222 004 R	IAM	MIRROR

General Specifications: 4D-554-0 - Size ISO 16405-1 E

Further Technical Data: 2020-10-28

Copyright WABCO®

WABCO
REMAN MAXX 22T ADB

Class to: 1, 50, 180, 400
 Fine: 0.5, 1.0, 1.5, 2.0
 Medium: 1.0, 2.0, 3.0, 4.0, ±3°
 Coarse: 2.0, 3.5, 5.0, 6.5

Scale: 1:1 (1:5)

Part No.: 640 222 003 R
 Date of 1st issue: 2019-09-10
 Doc. Code: 053 EN 1/1

Revision: 1
 Date: 2021

This document is the property of WABCO. It is intended for use by the customer only. It is not to be distributed outside the customer's organization. WABCO reserves the right to modify this document without notice. The customer is responsible for ensuring that the correct version of this document is used.