



	NOTE BEMERKUNG	TIGHTENING TORQUE ANZIEHMOMENT	WIDTH OVER FLATS SW
1	-	-	-
2	-	-	-
3	-	-	-
4	-	-	-
5	-	-	-

	NOTE BEMERKUNG	TIGHTENING TORQUE ANZIEHMOMENT	WIDTH OVER FLATS SW
21	-	-	-
22	-	-	-
23	-	-	-
24	-	-	-
25	-	-	-

- 6 MAX. ROTARY OUTLINE
MAXIMALE ROTATIONSKONTUR
- 7 MAX. DISPLACEMENT
MAXIMALE VERSCHIEBUNG
- 8 PERMISSIBLE FITTING DIMENSION OF THE DISC
ZULASSIGES SCHEIBENEINBAUSS
- 9 BRAKE DISC NEW 45-0.2 WEARABLE UP TO: 37
BREMSSCHEIBE NEU VERSCHLEISSBAR BIS:
- 10 ASSEMBLY DIMENSION FOR BRAKE PADS
EINBAUSS FÜR BREMSBELÄGE
- 11 - - -
- 12 FORWARD DRIVE - ROTATION DIRECTION
VORWAERTS DREHRICHTUNG
- 13 ENVELOPE CURVE CALIPER WITH COVER
HUELLKURVE BREMSSATTEL MIT DECKEL
- 14 ENVELOPE CURVE CARRIER
HUELLKURVE BREMSENTRAEGER
- 15 MAXIMUM DISC CLEARANCE
SCHEIBENFREIGANG
- 16 CENTER LINE CYLINDER
MITTE ZYLINDER
- 17 FOR SHIPMENT AND STORAGE
FLUR TRANSPORT UND LAGERUNG
- 18 HEXAGON WIDTH OVER FLATS
SECHSKANT SW
- 19 - - -
- 20 DETAILED INFORMATION FOR MARKING
DETAILLIERTE INFORMATIONEN ZUR KENNZEICHNUNG 640 175 060 0 DOC. CODE 922

- 26 - - -
- 27 - - -
- 28 - - -
- 29 - - -
- 30 - - -
- 31 - - -
- 32 - - -
- 33 - - -
- 34 - - -
- 35 - - -
- 36 BRAKE ACTUATOR SIZE RESTRICTION SEE PART SPECIFICATION 640 225 007 0 MAX. ACTUATOR TYPE 24
ZYLINDERANSCHLUSSMASSE NACH PART SPEZIFIKATION

COATING
ANTI-CORROSION PROTECTION - SALT SPRAY TEST MIN. 96 HOURS
BESCHICHTUNG
KORROSIONSSCHUTZ-SALZSPRUEHNEBELPRUEF. MIN. 96 STD.

640 225 041 0	MIRROR IMAGE SPIEGELBILD	PAN22-1 PRODUCT SPECIFICATION: 640 225 007 0 PRODUKT SPEZIFIKATION:	General Specification: ISO 8075, JIS-535-1, Sae ISO 14455 LP	Copyright WABCO®	WABCO DISC BRAKE PAN-RANGE LIGHT SCHEIBENREMSE PAN-REIHE LEICHT
640 225 040 0	AS SHOWN WIE GEZEICHNET		Dimensions in mm Class 10 ± 50 ± 80 ± 100 ± 120 ± 150 ± 200 ± 250 ± 300 ± 400 Fine ± 0.05 ± 0.1 ± 0.15 ± 0.2 Medium X ± 0.1 ± 0.2 ± 0.3 ± 0.4 ± 0.5 Coarse ± 0.2 ± 0.3 ± 0.5 ± 0.6 ± 0.8 Trapped Holes etc.	Date: 2023-02-15 Sheet: 1 of 1 Size: 1 x J Scale: 1:1 A O CREO	