


## Symbols & Signal Words



- ⚠ DANGER** Description of an immediate situation which will result in irreversible injury or death if the warning is ignored.
- ⚠ WARNING** Description of a possible situation which may result in irreversible injury if the warning is ignored.
- ⚠ CAUTION** Description of a possible situation which may result in irreversible injury or death if the warning is ignored.
- Parts having item numbers with circles are included in the kit.

- i** Instruction / Information for a correct repair
-  The kit can be used for devices according table.
- T** Tighten element with specified torque or angle of rotation.
- NOTE** Instruction / Information for a correct repair

## General Repair Hints

- Only qualified personnel of a specialist workshop are authorized to perform repair work on a vehicle's security system.
- Absolutely follow specifications and instructions of vehicle manufacturer.
- Keep to company's relevant accident prevention regulations and national regulations.
- Use only spare parts released by WABCO or vehicle manufacturer.
- Always start repair work only when you have read and understood all information required for repair. Documents additionally needed: Test Instruction, Spare Parts List, General Repair and Test Hints (815 010 109 3) to be found on [www.wabco-auto.com](http://www.wabco-auto.com) by entering product number of the device or the publication number in INFORM.
- Check each repaired equipment for functional efficiency and tightness on an adequate facility according to the test instruction.
- WABCO does not accept any liability or responsibility for the quality or functionality of a repaired device

## Sequence of assembly

Picture	Symbol	Procedure	Item	Sequence:	Torque:	Rotation angle:	Comments
<b>1</b>	<b>T</b> 1	1	12		38 ± 4 Nm		Ensure accurate torque at all screws before next step.
	<b>T</b> 2	2	17		38 ± 4 Nm		Ensure accurate torque at all screws before next step.
<b>1+2</b>	<b>T</b> 3	3	9	1, 2, 3, 4	20 ± 2 Nm		Ensure accurate torque at all screws before next step.
<b>1+2</b>		4	9	1, 2, 3, 4		90° +10° / -5°	Carry out the steps of this procedure one after the other
<b>1+2</b>	<b>T</b> 4	5	8	5, 6	6 ± 0.6 Nm		Ensure accurate torque at all screws before next step.
<b>1+2</b>		6	8	5, 6		90° + 10° / -0°	Carry out the steps of this procedure one after the other
<b>1</b>	<b>T</b> 5	7	18		200 ± 10 Nm		Ensure accurate torque at all screws before next step.
<b>1</b>	<b>i</b> 1	8	15				Applicable only if the shaft contains slot for Woodroof key
<b>1</b>	<b>i</b> 2		X				Lubricate sealing and sliding surfaces.100942180