


Non e permesso consegnare a terzi o riprodurre questo documento, ne utilizzarne il contenuto o renderlo comunque noto a terzi senza autorizzazione esplicita. Ogni infrazione costituirà un evidente abuso e comporterà il risarcimento dei danni subiti. E' fatto riserva di tutti i diritti derivanti da brevetti o modelli.


Toute Communication ou reproduction de ce document, toute exploitation ou communication de son contenu sont interdites, sauf autorisation expresse. Tout manquement a cette regle constitue un abus evident et expose son auteur au versement de dommages et interets. Tous droits de propriete industrielle reserves, notamment en matiere de brevets et de modesles.

Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Controvention of this restriction will constitute an evident abuse and result in a liability to the payment of damages. All rights are reserved in the event of the grant of patent or registration of a utility model or design. This document is the subject of copyright.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen stellen einen offensichtlichen Missbrauch dar und verpflichten zu Schadensersatz. Alle Rechte fuer den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.



* ALTERNATIVE DIAMETER: Ø10.5




MATERIAL OF HOUSING AND NUT: CuZn
WORKING TEMPERATURE: -40°C...+100°C
WORKING PRESSURE: MAX 15 bar

CLEANLINESS REQUIREMENT:
NO PARTICLES >1MM ALLOWED ACC. TO MANDATORY STANDARD JED-334 AND JED-593
AREA: FOR THE WHOLE PART (SPECIAL AGREEMENTS POSSIBLE, TO BE AGREED WITH PRODUCT ENGINEERING)
GENERAL SPECIFICATION : JED-762 ; JED-622
ENGINEERING RELATED AGREEMENTS WITH SUPPLIER HAVE TO BE MENTIONED IN THE "RELEASE OF SUPPLIER"
M12x1.5 TORQUE WITHOUT LUBRICATION NOMINAL 20Nm (24Nm MAX.)
FOR USE IN APPLICATION IN COMPRESSED AIR SYSTEMS IN COMMERCIAL VEHICLES :
- WITH COMPRESSED AIR ACC. JED-848

General Specification: JED-334-1 , Size ISO 14405 LP						Copyright WABCO®			WABCO PUSH-IN COUPLING										
Further Technical Data:						Date		Signature											
Doc. Code:		Sheet: To				Drawn													
General Tolerances JED-261						Checked													
Range of Nominal Dimensions (± mm)																			
Class 1)						Expert													
						Szczulkowski													
Fine		X	0.5	1.0	1.5	2.0	Mass		Scale		Material No.		Date of first issue:						
Medium			1.0	2.0	3.0	4.0	0.062 KG		2:1 1:1		893 501 005 4		Doc.Code	Language	Sheet				
Coarse			2.0	3.5	5.0	6.5							005	EN	1/1				
Tapped Holes acc. JED-152						A 3		CREO				ECN-No.		Revision		Techn. Resp.		Replacement for	
1) Tolerance Class Applied Crossmarked												-		-		5790		-	

893 501 005 4



100mm