

Non e permesso consegnare a terzi o riprodurre questo documento, ne utilizzarne il contenuto o renderlo comunque noto a terzi senza autorizzazione esplicita. Ogni infrazione costituisce un evidente abuso e comportera il risarcimento dei danni subiti. E' fatto riserva di tutti i diritti derivanti da brevetti o modelli.

Toute Communication ou reproduction de ce document, toute exploitation ou communication de son contenu sont interdites, sauf autorisation expresse. Tout manquement a cette regle constitue un abus evident et expose son auteur au versement de dommages et interets. Tous droits de propriete industrielle reserves, notamment en matiere de brevets et de modesles.

Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Controvention of this restriction will constitute an evident abuse and result in a liability to the payment of damages. All rights are reserved in the event of the grant of patent or registration of a utility model or design. This document is the subject of copyright.

Weitergabe sowie Vervielfaeligung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdruecklich zugestanden. Zuwiderhandlungen stellen einen offensichtlichen Missbrauch dar und verpflichten zu Schadensersatz. Alle Rechte fuer den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

1	2	3	4	5	6	7	8				
A	B	C	D	E	F	G	H	I	J	K	
for Tube 8x1,0 new Line <CI> ⓑ	M12x1,5	8	Hex.18	Ø17,4	33,3	20Nm (24Nm)	(20,5) Push in length <CI> ⓑ	1,5	Ø18,3	with O-ring	

G : recommended torque without lubrication (max. torque) respect max torque of counter part

Cleanliness requirement:

Class: K00 according JED-593

Area: for the whole part (Special agreements possible;
to be agreed with Product Engineering)

Material:

- 1 CuZn
- 2 PA (inner components)
- 3 EPDM


General Specification : JED-762 ; JED-622 ; JED-220

Engineering related agreements with Supplier have to be mentioned in the "Release of Supplier"

For use in application in compressed air systems in commercial vehicles :

- with Polyamind or Hytrel tubes acc. ISO7628; DIN74324, DIN73378
- with compressed air acc. JED-848
- at working conditions (consider tube spec.) :

- -40 °C ... 100 °C
- max. 12,5 bar



1:1

General Specification: JED-334-1 , Size ISO 14405 LP										Copyright WABCO®				WABCO Screw-in Fitting													
Further Technical Data:										Date		Signature															
Doc. Code:				Sheet:		To		Drawn		2019-11-28		Balaga															
General Tolerances										Checked		2019-12-11								Szczulkowski							
										Expert		Szczulkowski															
		Range of Nominal Dimensions (± mm)																									
Class	1)	≤ 50	> 50 ≤ 180	> 180 ≤ 400	> 400																						
Fine	X	0.5	1.0	1.5	2.0	±3°		Mass		Scale		Material No.															
Medium		1.0	2.0	3.0	4.0			0.028 KG		2:1 1:1		893 800 007 2															
Coarse		2.0	3.5	5.0	6.5			Size		CAD System																	
Tapped Holes acc. -										A 3		CREO				ECN-No.		Revision		Techn. Resp.		Date of first issue: 2007-01-16					
1) Tolerance Class Applied Crossmarked																502571		2 x B		5790		Doc.Code		Language		Sheet	
																						005		EN		1/1	
																								Replacement for			

893 800 007 2

502571

2 x B

5790

005 EN 1/1