


Non e permesso consegnare a terzi o riprodurre questo documento, ne utilizzarne il contenuto o renderlo comunque noto a terzi senza autorizzazione esplicita. Ogni infrazione costituisce un evidente abuso e comportera il risarcimento dei danni subiti. E' fatto riserva di tutti i diritti derivanti da brevetti o modelli.

Toute Communication ou reproduction de ce document, toute exploitation ou communication de son contenu sont interdites, sauf autorisation expresse. Tout manquement a cette regle constitue un abus evident et expose son auteur au versement de dommages et interets. Tous droits de propriete industrielle reserves, notamment en matiere de brevets et de modesles.

Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Controvention of this restriction will constitute an evident abuse and result in a liability to the payment of damages. All rights are reserved in the event of the grant of patent or registration of a utility model or design. This document is the subject of copyright.

Weitergabe sowie Vervielfaeltigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdruecklich zugestanden. Zuwiderhandlungen stellen einen offensichtlichen Missbrauch dar und verpflichten zu Schadenersatz. Alle Rechte fuer den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

1	2	3	4	5	6	7	8	
A	B	C	D	E	F	G	H	I
FOR TUBE Ø12	M22x1,5	12	Hex 27	M18x1,5	29	11	STRAIGHT	TYPE ISO8434-1 SDS
		A		A	A	A	A	A



OPTIONALLY IDENTIFICATION : MANUFACTURER
WAHLWEISE KENNZEICHNUNG : HERSTELLER
FACULTATIF INDICATIONS : FABRICANT
FACULTATIVA INDICAZIONE : PRODUTTORE

CLEANLINESS REQUIREMENT:

NO PARTICLES >1MM ALLOWED ACC. TO MANDATORY STANDARD:
JED-334 AND JED-593

AREA: FOR THE WHOLE PART (SPECIAL AGREEMENTS POSSIBLE;
TO BE AGREED WITH PRODUCT ENGINEERING)

MATERIAL : STEEL
SURFACE PROTECTION : gal Zn CrVI free

GENERAL SPECIFICATION : JED-762 ; JED-622 ; JED-220


ENGINEERING RELATED AGREEMENTS WITH SUPPLIER HAVE TO BE MENTIONED
IN THE "RELEASE OF SUPPLIER"

FOR USE IN APPLICATION IN COMPRESSED AIR SYSTEMS IN COMMERCIAL VEHICLES :

- WITH COMPRESSED AIR ACC. JED-848

- AT WORKING CONDITIONS:

- -40 °C ... 100 °C
- MAX. 12,5 bar



1:1

A

General Specification: JED-334-1 , Size ISO 14405 LP						Copyright WABCO®			WABCO										
Further Technical Data:						Date		Signature											
Doc. Code:						Sheet: To													
												General Tolerances JED-261							
Class 1)		Range of Nominal Dimensions (± mm)				2019-11-21		Balago		Fitting Verschraubung Raccords Raccordo									
		≤ 50		> 50 ≤ 180		> 180 ≤ 400		> 400					Checked						
		≤ 50		≤ 180		≤ 400		> 400					2019-12-16		Szczykowski				
		≤ 50		≤ 180		≤ 400		> 400					Expert						
		≤ 50		≤ 180		≤ 400		> 400					Szczykowski						
Fine		X	0.5	1.0	1.5	2.0	Mass		Scale		Material No.		Date of first issue: 2007-10-09						
Medium			1.0	2.0	3.0	4.0	0.06 KG		2:1 (1:1)		893 900 017 4		Doc.Code		Language		Sheet		
Coarse			2.0	3.5	5.0	6.5	Size		CAD System				005		ML		1/1		
Tapped Holes acc. JED-152						A 3		CREO				ECN-No.		Revision		Techn. Resp.		Replacement for	
1) Tolerance Class Applied Crossmarked												169270		8 x A		5790			

100mm