

Non e permesso consegnare a terzi o riprodurre questo documento, ne utilizzare il contenuto o renderlo comunque noto a terzi senza autorizzazione esplicita. Ogni infrazione costituirà un evidente abuso e comporterà il risarcimento dei danni subiti. E' fatta riserva di tutti i diritti derivanti da brevetti o modelli.

Toute communication ou reproduction de ce document, toute exploitation ou communication de son contenu sont interdites, sauf autorisation expresse. Tout manquement a cette regle constitue un abus evident et expose son auteur au versement de dommages et interets. Tous droits de propriete industrielle reserves, notamment en matiere de brevets et de modesles.


Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Contravention of this restriction will constitute an evident abuse and result in a liability to the payment of damages. All rights are reserved in the event of the grant of patent or registration of a utility model or design. This document is the subject of copyright.

Weitergabe sowie Vervielfaeltigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdruerklich zugestanden. Zuwiderhandlungen stellen einen offensichtlichlichen Missbrauch dar und verpflichten zu Schadenersatz. Alle Rechte fuer den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.

1	2	3	4	5	6	7	8
A	B	C	D	E	F	G	
Ø8,8	1/4''-18 NPTF	14	Hex.18	Ø17,3	40,6	24Nm (28Nm)	


G : recommended torque without lubrication (max. torque) respect max torque of counter part

* circular sealing edge free from scratches or damages



For use in application in compressed air systems in commercial vehicles :

- with Polyamind or Hytrel tubes acc. ISO7628; DIN74324, DIN73378
- with compressed air acc. JED-848
- at working conditions (consider tube spec.) :
 - -40 °C ... 100 °C (storage 130 °C max. 2h)
 - max. 1250kPa



1:1

Cleanliness requirement:

Class: K00 according JED-593

Area: for the whole part (Special agreements possible; to be agreed with Product Engineering)

Material:

- 1 CuZn
- 2 EPDM

General Specification : JED-762 ; JED-622 ; JED-271 ; JED-220

Engineering related agreements with Supplier have to be mentioned in the "Release of Supplier"

General Specification: JED-334-1 , Size ISO 14405 LP						Copyright WABCO®		WABCO Quick Coupling											
Further Technical Data:						Date						Signature							
Doc. Code:		Sheet:		To		Drawn													
2015-02-11		2015-02-11		Szczutkowski		Checked													
2015-02-16		2015-02-16		Stephan		Expert													
Kaufmann		Kaufmann		Kaufmann		Kaufmann													
General Tolerances						Mass		Scale		Material No.		Date of first issue: 2015-02-16							
Class 1)		Range of Nominal Dimensions (± mm)				0.031 KG		2:1 1:1		893 920 374 2		Doc.Code		Language		Sheet			
Fine		X	0.5	1.0	1.5	2.0							005		EN		1/1		
Medium			1.0	2.0	3.0	4.0													
Coarse			2.0	3.5	5.0	6.5													
Tapped Holes acc. -						Size		CAD System				ECN-No.		Revision		Techn. Resp.		Replacement for	
1) Tolerance Class Applied Crossmarked						A 3		CREO				-		-		5790			