

WABCO


TECHNICAL DATA

senza autorizzazione esplicita. Ogni infrazione costituirà un evidente risarcimento dei danni subiti. E' fatta riserva di tutti i diritti derivanti da document, and giving it to others and the use or communication of the document, and giving it to others and the use or communication of this restriction will be prohibited without express authority. Contravention of this restriction will result in a liability to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of an utility model or design.

<u>159 CM³ SINGLE CYLINDER COMPRESSOR</u>	
Bore and Stroke	75 Bore x 36 mm stroke
Swept Volume	159 CM ³
Air Output at 8 Bar and 2600 R.P.M. and 20°C Ambient temperature	230 L/Min. with air temperature at delivery port of 200°C
Normal Max. Speed	2890 R.P.M.
Maximum over-run speed	3320 R.P.M.
Normal maximum working pressure	11 bar
Environmental Temperature range	-40°C to 80°C
Type of Head cooling	Water. Flow rate 6 litres/min. Temperature 93°C maximum
Air Output Control	Governor Valve
Type of Mounting	Flange
Mounting Position	Vertical - 26° each side of vertical
Type of Drive	Gear Coupled
Lubrication	Pressure fed from engine Min. pressure 2.5 bar Oil temperature 107°C max
Oil Drain	Through mounting flange

DTU

DCN-No	REV	DATE	TRI: 300 DATE 17.8.92	IDENTIFICATION	
				CODE FOR DOCUMENT	SHEET
				605	2 /k
			911 145 005 0		



interdites, sauf autorisation expresse. Tout manquement à cette règle et exposé son auteur au versement de dommages et intérêts. Tous droits réservés, notamment en matière de brevets et de modèles.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwidernhandlungen lichen Mißbrauch darf und verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung vorbehalten.