




THERMAL RANGE OF APPLICATION :
THERMISCHER ANWENDUNGSBEREICH : -40°C...+80°C
BAMME D'APPLICATION TERMIQUE :
CAMPO DI APPLICAZIONE TERMICA :


PORT	:	SPRING BRAKE CYLINDER, WORKING PRESSURE	:		(TEMPORARILY	:	
ANSCHLUSS	:	FEDERSPEICHERZYLINDER, BETRIEBSDRUCK	:	Pe max. = 8.5 bar	(KURZZEITIG	:	Pe max. = 11 bar)
ORIFICE	:	CYLINDRE A RESSORT, PRESSION D'UTILISATION	:		DE COURTE DUREE	:	
ORIFIZIO	:	CILINDRO A MOLLA, PRESSIONE D'ESERCIZIO	:		BREVE TEMPO SOLO:	:	

SEE TECHNICAL INFORMATION SHEET :
 *** SIEHE KONSTRUKTIONSBLATT : 826 102 526 3
 VOIR NOTICE TECHNIQUE :
 VEDERE FASCICOLO DESCRITTI :

 $0^\circ \pm 5^\circ$

FIXTURE OF RELEASE BOLT
 LOSESCHRAUBENHALTER
 SUPPORT DE LA VIS DE DESSERRAGE
 SUPPORTO DI VITE DE RILASCIO


NAME PLATE
BEZEICHNUNGSSCHILD
PLAQUE DE FIRME
TARGHETTA



TO BE INSTALLED WITH LOWER BREATHER HOLE OPEN
IM EINBAUZUSTAND UNTERE ATMUNGSBOHRUNG OFFEN
A MONTER AVEC LE RENIFLARD INFÉRIEUR OUVERT
INSTALLAZIONE CON IL FORO DI SFIATO INFERIORE APERTO


☒ RELEASE POSITION
LOESESTELLUNG
POSITION DE DESSERRAGE
POSIZIONE DI RILASCIO

DRIVING POSITION
FAHRTSTELLUNG
POSITION DE MARCHÉ
POSIZIONE DI MARCIA



ADMISSIBLE INSTALLATION POSITION
ZULAESSIGE EINBAULAGE
POSITION D'INSTALLATION ADMISE
POSIZIONE DI MONTAGGIO AMMESSA

STROKE : 11 = min. 75 mm
HUB :
COURSE : 12 = min. 75 mm
COSA :

[illegible]