


[illegible][illegible]

①									
925 488 026 0	A 021 420 32 18				14/24		B.15	A	95.6
925 488 025 0	A 021 420 31 18	re			14/24		8.1	A	95.6
925 488 024 0	A 021 420 30 18	li			14/24		8.1	A	95.6
925 488 023 0	A 020 420 78 18	re			14/24		8.1	A	95.6
925 488 022 0	A 020 420 76 18	li			14/24		8.1	A	95.6
925 488 021 0	A 020 420 74 18	li			14/24		8.1	A	95.6
925 488 020 0	A 020 420 73 18	re			14/24		8.1	A	95.6
925 488 015 0	A 019 420 50 18	li			14/24	H1	8.2	A	95.6
925 488 014 0	A 019 420 51 18	re			14/24	H1	8.2	A	95.6
925 488 013 0	A 015 420 58 18	li			14/24	H1	8.2	B	94
925 488 012 0	A 015 420 57 18	re			14/24	H1	8.2	B	94
925 488 010 0	A 020 420 75 18				14/24	H2	8.15	A	95.6
WABCO	CUSTOMER'S NO. KUNDEN-NR. No. CLIENT No. CLIENTE	AUSFÜHRUNG	ZGS	CAD	TYPE TYP TYPE TIPO	SUPPORT HALTER SUPPORT SUPPORTO	MASS GEWICHT MASSE Mасса (kg)	VARIANT ABWÄNDUNG VARIANTE VARIANTE	P
IDENTIFICATION									
9	10				11	1	12		

General Specification: ED-334-0		Copyright: WABCO			
Further Technical Data:		Date: 07.09.2006			
Doc. Code:	Doc. Name:	Sheet:	To:	Date: 07.09.2006	
General Technical Data: ED-261					
Range of Nominal Dimensions (x ± mm)					
Proc. 11	± 50	± 50	± 100		
Proc. 12	± 50	± 50	± 100		
Proc. 13	0,5 - 1,0	1,5 - 2,0	3,0 - 4,0		
Medium X	1,0 - 2,0	2,0 - 3,0	3,0 - 4,0		
Medium Y	1,0 - 2,0	2,0 - 3,0	3,0 - 4,0		
Medium Z	1,0 - 2,0	2,0 - 3,0	3,0 - 4,0		
Exempted holes are: ED-261					
T1: Tolerance Class: Applied Overdimensioned					