



SERVICE PRESSURE :
 BE TRIEBSDRUCK : MAX 20bar
 PRESSION DE SERVICE :
 PRESSIONE D'ESERCIZIO:

MEDIUM : AIR
 MEDIUM : LUFT
 MILIEU : AIR
 FLUIDO : ARIA

CONNECTIONS: = SUPPLY
 ANSCHLUESSE: = LUFTEINTRITT
 ORIFICES: 1, 11, 12 = ALIMENTATION
 ORIFIZI: = ALIMENTAZIONE

= CIRCUIT 1
 21 = KREIS 1
 = CIRCUIT 1
 = CIRCUITO 1

= CIRCUIT 2
 22 = KREIS 2
 = CIRCUIT 2
 = CIRCUITO 2

= CIRCUIT 3
 23 = KREIS 3
 = CIRCUIT 3
 = CIRCUITO 3

= CIRCUIT 4
 24 = KREIS 4
 = CIRCUIT 4
 = CIRCUITO 4

CIRCUIT KREIS CIRCUIT CIRCUITO	21	22	23	24
OPENING PRESSURE [bar] OEFFNUNGSDRUCK [bar] PRESSION D'OUVERTURE [bar] PRESSIONE DI APERTURA [bar]	7,0,3			
CLOSING PRESSURE DYNAMIC [bar] SCHLISSDRUCK DYNAMISCH [bar] PRESSION DE FERMETURE DYNAM. [bar] PRESSIONE DI CHIUSURA DINAM. [bar]	≅ 5			
CLOSING PRESSURE STATIC [bar] AT FAILURE OF CIRCUIT SCHLISSDRUCK STATISCH [bar] BEI AUSFALL VON KREIS PRESSION DE FERMETURE STAT. [bar] EN CAS DE DEFAILLANCE DU CIRCUIT PRESSIONE DI CHIUSURA STATICO [bar] IN CASO DI DIFETTO DEL CIRCUITO	0	≅ 4,5	≅ 6,7	
	≅ 4,5	0	≅ 6,7	
	4,5 ^{+0,5}	0	4,5 ^{+0,5}	
	4,5 ^{+0,5}	4,5 ^{+0,5}	0	

*) OPENING PRESSURE = MAINTAINED PRESSURE
 OEFFNUNGSDRUCK = GESICHERTER DRUCK
 PRESSION D'OUVERTURE = PRESSION MAINTENUE
 PRESSIONE DI APERTURA = PRESSIONE MANTENUTA

ADMISSIBLE TEMPERATURES
 THERMISCHER ANWENDUNGSBEREICH - 40°...+90°
 TEMPERATURE DE SERVICE
 TEMPERATURA D'ESERCIZIO

DATE		SIGNATURE		WESTINGHOUSE	
79-01-17		<i>Mudrich</i>		PROTECTION VALVE (FOR 4 CIRCUITS)	
79-01-17		<i>Barr</i>		VALVE DE PROTECTION (A 4 CIRC.)	
79-01-30		<i>Pantev</i>		VALVOLA DI PROTEZIONE (A 4 CIRC.)	
19866	1 x B	79-05-10		SCHUTZVENTIL (FUER 4-KREIS-ANL.)	
19860	1	79-04-18			
19850	1 B	79-03-29			
19843	1 A	79-02-15			
A 2		140	1:1	934 702 221 0	
				6 05	

All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.
 Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.