



A
1:1
3-PLACES

- 1 METRIC PORT M22x1.5 ACCORDING TO ISO 4039-2
 - 2 PART IDENTIFICATION LABEL
- GENERAL SPECIFICATION ACCORDING TO EN 286-2:1992

SL.NO.		NOTES
1	CAPACITY	10 Litres
2	WORKING PRESSURE	20 bar
3	TEMPERATURE RANGE	-50°C TO +100°C
4	MATERIAL	STEEL
5	SURFACE PROTECTION	PAINT - BLACK (RAL 9005)
6	CORROSION RESISTANCE	480 hours ACCORDING TO ISO 9227
7	PERMISSIBLE INSTALLATION	DRAIN VALVE SHOULD FACE DOWNWARDS IN VEHICLE ASSEMBLY

ORSAN	
TYPE	6T1541001-1
WABCO	9502100000
T min	-50°C
T max	+100°C
Vol	5.3 litres
Ps	20 bar
Norm	EN 286-2:1992
Prod. Date	YYYYMMDD & S.No.

General Specification: JED-334-1, Size ISO 14405 LP		Copyright WABCO®		WABCO	
Further Technical Data:		Date	Signature		
Doc. Code:	Sheet:	To	Drawn	AIR RESERVOIR	
General Tolerances JED-261			2020-09-16		
Range of Nominal Dimensions (± mm)			Checked	Schul Homeed	
Class 1)	≤ 50	> 50 ≤ 180	2020-09-16		
Fine	0.5	1.0	1.5	2.0	Expert
Medium	1.0	2.0	3.0	4.0	Material No.
Coarse	X 2.0	3.5	5.0	6.5	950 210 000 0
Tapped Holes acc. ISO 4039-2 (A)			Mass	Scale	Date of first issue: 2020-09-11
1) Tolerance Class Applied Crossmarked			5.3	1:2	Doc.Code
			kg	1:1	Language
			Size	CAD System	Sheet
			A 2	CREO	005
			ECN-No.		EN
			Revision		1/1
			Techn. Resp.		5060
			Replacement for		

Non e permesso copiare, o terzi o riprodurre questo documento, ne utilizzare il contenuto o renderlo comunque noto a terzi senza autorizzazione esplicita. Ogni infrazione costituisce un evidente abuso e comporterà il risarcimento dei danni subiti. E' fatta riserva di tutti i diritti derivanti da brevetti o modelli.

Toute communication ou reproduction de ce document, toute exploitation ou communication de son contenu sont interdites, sauf autorisation expresse. Tout manquement a cette regle constitue un abus evident et expose son auteur au versement de dommages et interets. Tous droits de propriete industrielle reserves, notamment en matiere de brevets et de modesles.

Alle Rechte hier den Fall der Patentierung oder Gebrauchsmuster-Eintragung vorbehalten.