



A
2:1
4-PLACES

- ① METRIC PORT M22x1.5 ACCORDING TO ISO 4039-2
 - ② IDENTIFICATION LABEL
- GENERAL SPECIFICATION ACCORDING TO EN 286-2

SL.NO.	NOTES	
1	CAPACITY	10 Litres
2	WORKING PRESSURE	15.5 bar
3	TEMPERATURE RANGE	-50°C TO +100°C
4	MATERIAL	STEEL
5	SURFACE PROTECTION/COLOR:	PAINT / BLACK
6	EXTERNAL SURFACE PROTECTION	480 HOURS NSS TEST ACC. DIN EN ISO 9227
7	PERMISSIBLE INSTALLATION	DRAIN VALVE SHOULD FACE DOWNWARDS IN VEHICLE ASSEMBLY

SUPPLIER NAME

TYPE	6T2061016-1
WABCO	9504050070
T min -50°C	T max +100°C
Vol 10 litres	Ps 15.5 bar
Norm	EN 286-2:1992
Prod. Date	YYYYMMDD & S.No

General Specification: JED-334-1 - Size ISO 14405 LP		Copyright WABCO®	
Further Technical Data:		Date	Signature
Doc. Code:	Sheet: To	2020-08-12	Christosolomon D
General Tolerances JED-261		Checked:	
Range of Nominal Dimensions (± mm)		2020-08-13	
Class	1) ≤ 50 > 50 > 180 > 180 > 400 > 400	Expert:	
Fine	0.5 1.0 1.5 2.0	Sahul Homeed	
Medium	1.0 2.0 3.0 4.0	Mass	Scale
Coarse	2.0 3.5 5.0 6.5	4.7 kg	1:2
Tapped Holes acc. ISO 4039-2		Size	CAD System
1) Tolerance Class Applied Crossmarked		A 1	CREO
		Material No.	
		950 405 007 0	
		Date of first issue:	2020-08-12
		Doc. Code	Language
		005	EN
		Revision	Techn. Resp.
			5060
		Replacement for	

Tutti i diritti sono riservati. È vietata espressamente la ristampa o l'uso non autorizzato senza permesso scritto dalla WABCO. La WABCO non è responsabile per danni materiali o morali. La WABCO non è responsabile per danni materiali o morali. La WABCO non è responsabile per danni materiali o morali.