



NOTES:

1. MINIMUM PRESSURE AT MAXIMUM EXTENSION IS NOT TO BE LESS THEN 0.5bar.
2. ASSEMBLY PRESSURE TESTED PER GMS XIII-301.
3. ASSEMBLY DESIGNED TO OPERATE BETWEEN -40° AND +70°.
4. CUSTOMER TO PROVIDE MECHANICAL DEVICE TO LIMIT MAXIMUM EXTENSION TO MAX. EXTENDED HEIGHT.
5. WARNING: DO NOT INFLATE UNLESS FULLY SECURED IN THE SUSPENSION OR OTHER ADEQUATE STRUCTURE. DO NOT INFLATE TO MORE THEN 7bar AT ANY HEIGHT. OTHERWISE BODILY INJURY COULD RESULT

SURFACE TREATMENT:
- UPPER BEAD PLATE: Zinc coating

Item	Qty	Description	Standard	Material
6	1	WARNING & IDENT. LABEL		
5	1	NUT M12 + STEEL PLATE	ASB-20-9-284	US113
4	1	LOWER RETAINER + BUMPER	ASC-20-6-190	Steel & SBR
3	1	UPPER BEAD PLATE	ASA-92-8-730	U St 13
2	1	PISTON	ASD-20-7-235	COMPOSITE
1	1	FLEXMEMBER	566-24-3-522	NR-BR

Dimensions without tolerancing	2006	Date	Name	Signature
20.06	Designed	20.06.	J. Rebernik	
20.06	Checked	20.06.	M.Košir	
27.06	Approved	20.06.	M.Košir	

Scale: 1:2(A2)

Weight(kg): 6.6

Belong to: AIR SPRINGS

Title: WABCO 951 812 739 0 (GY 1R12-739)

Revision: 01 01.08.06

Signature:

Revision	Date	Name	Change
01	01.08.06	J.Rebernik	Part list corrected, leader text changed - now 2xM12x1.75...



GOODYEAR ENGINEERED PRODUCTS EUROPE
Družba za proizvodnjo gumnih izdelkov, d.o.o.

Drawing number: 566-24-2-793