


LOCKED POSITION
VERRASTERTE STELLUNG
POSITION VERROUILLEE
POSIZIONE BLOCCARE

30 JAN. 1997

	STANDARD, VERSION STANDARDAUSFÜHRUNG VERSION NORMALE VERSIONE NORMALE	T °C -40° +80°
MEDIUM FLUIDE FLUIDO	COMPRESSED AIR DRAHTLUFT AIRA COMPRESA	
MAXI NET PRESSURE MAX BETRIEBSDRUCK PRESSION MAXIMUM D'ALIMENTATION PRESSION MASSIMA D'ALIMENTAZIONE	P ₁ MAX BARS	20
ABSTRACTING ENTNEHMUNG REGULAZIONE	INLET PRESSURE EINSTRÖMUNGSDRUCK PRESSION D'ALIMENTATION PRESSIONE D'ALIMENTAZIONE P ₁ = 15 ÷ 30 BAR	DELIVER PRESSURE ABGABEDRUCK PRESSION DÉLIVRÉE PRESSIONE LUBRIFICAZIONE P ₂ = 7,5 ÷ 15 BAR
VORWARTS CHONEN ENHÄLTUNG POSIZIONE DI FUNZIONAMENTO	IMPORTANT BESONNIGKEIT DIFFERENTE MODIFICATE	
1 INLET VORWARTSABSCHLUSS ALIMENTAZIONE		
2 DELIVERY ABGESTÜRZTE LUFT ENTNEHMUNG UTILIZZAZIONE		
3 EXHAUST ABZUG SCARICO		

[illegible]