

MEDIUM : AIR
 MEDIUM : LUFT
 FLUIDE : AIR
 FLUIDO : ARIA

MAX. ADMISSIBLE PRESSURE :
 MAX. ZULÄSSIGER DRUCK : $P_e \leq 25 \text{ bar}$
 PRESSION ADMISSIBLE MAXI. :
 PRESSIONE AMMISSIBILE MAX. :

THERMAL RANGE OF APPLICATION :
 THERMISCHER ANWENDUNGSBEREICH :
 GAMME D'APPLICATION THERMIQUE :
 CAMPO DI APPLICAZIONE TERMICA :

AMBIENT TEMPERATURE :
 UMGEBUNGSTEMPERATUR : $-40^\circ\text{C} \dots +100^\circ\text{C}$
 TEMPERATURE AMBIANTE :
 TEMPERATURA AMBIENTE :

MEDIUM TEMPERATURE :
 MEDIUMTEMPERATUR : $-40^\circ\text{C} \dots +150^\circ\text{C}$
 TEMPERATURE DU FLUIDE :
 TEMPERATURA DEL FLUIDO :

CUT-OUT PRESSURE :
 ABSCHALTD RUCK :
 PRESSION D'OUVERTURE : $P_e = 8,5 \pm 0,2 \text{ bar}$
 PRESSIONE D'APERTURA :

PRESSURE SETTING RANGE :
 SCHALTSPANNE :
 PLAGE DE REGULATION : $\Delta p = 0,7 \begin{matrix} +0.5 \\ 0 \end{matrix} \text{ bar}$
 GAMMA DI REGOLAZIONE :

OPENING PRESSURE OF THE SAFETY VALVE (INTEGR) :
 ÖFFNUNGSDRUCK D. SICHERHEITSVENTILS (INTEGRIERT) :
 PRESSION D'OUVERTURE DE LA SOUPEPE : $P_{se} = 12 \begin{matrix} +2 \\ 0 \end{matrix} \text{ bar}$
 PRESSIONE D'APERTURA DELLA VALVOLA DI SICUREZZA :

Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Contravention of this restriction will constitute an evident abuse and result in a liability in the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of an utility model or design.

(E) (A)	TRI	140	IDENTIFICATION 975 303 463 0	TECHNICAL DOCUMENT 605	SHEET 2 / 2
	DATE	82-03-31			
CHANGE No. / LETTER	DATE				