
# **ProVia Clutch Servo for Japanese Range**

Provia Clutch Servo has an universal design to cover multiple Japanese OE devices. Range of highly reliable Clutch Servos with consistent quality level, zero compromise on safety choice.

#### Cross references

| 7         | ProVia part number | OE part number |  |  |
|-----------|--------------------|----------------|--|--|
| Eclic ora | PRO 411 100 0      | 642-09402      |  |  |
| 4         | PRO 4111010        | 642-09404      |  |  |
|           | PRO 411102 0       | 642-09306      |  |  |
|           | PRO 411103 0       | 642-09204      |  |  |
|           | PRO 411 200 0      | 642-09102      |  |  |
|           | PRO 4112010        | 642-09008      |  |  |







Engineered, tested
and approved by
Aftermarket specialists
for Aftermarket needs





### **Technical Attributes**

| Technical Attribute     | PRO 411 100 0   | PRO 411 101 0   | PRO 411 102 0    | PRO 411 103 0    | PRO 411 200 0    | PRO 411 201 0    |
|-------------------------|-----------------|-----------------|------------------|------------------|------------------|------------------|
| Variants                | 105 mm          | 105 mm          | 90 mm            | 70 mm            | 90 mm            | 70 mm            |
| Mounting                | 4x M10x1.25     | 4x M10x1.25     | 4x M10x1.25      | 4x M8x1.25       | 4x M10x1.25      | 4x M8x1.25       |
| Distance between holes  | 96.1± 0.3       | 96.1±0.3        | 85.5 ± 0.3       | 68.6 ± 0.3       | 85.5 ± 0.3       | 68.6 ± 0.3       |
| Oil inlet               | Port 14         | Port 14         | Port 14          | Port 14          | Port 14          | Port 14          |
| Push-rod thread         | Ball Ø10 mm     | Ball Ø10 mm     | Ball Ø10 mm      | Ball Ø10 mm      | Ball Ø10 mm      | Ball Ø10 mm      |
| Port Thread 14          | M12x1.5         | M12x1.5         | M12x1.5          | M12x1.5          | M12x1.5          | M12x1.5          |
| Fluid type              | Brake fluid     | Brake fluid     | Brake fluid      | Brake fluid      | Brake fluid      | Brake fluid      |
| Length                  | 280 ± 10        | 334 ± 10        | 273 ± 10         | 276 ± 10         | 266 ± 10         | 266 ± 10         |
| Max. operating pressure | 10.0 bar        | 10.0 bar        | 10.0 bar         | 10.0 bar         | 10.0 bar         | 10.0 bar         |
| Stroke                  | 35 ± 3 mm       | 44 ± 3 mm       | 35 ± 3 mm        | 35 ± 3 mm        | 35 ± 3 mm        | 35 ± 3 mm        |
| Port Thread 32          | M10X1.25        | M10X1.25        | M10X1.25         | M10X1.25         | M8X1             | M8X1             |
| Ports                   | M12x1.25        | M12x1.25        | M12x1.5, M14x1.5 | M12x1.5, M14x1.5 | M12x1.5, M14x1.5 | M12x1.5, M14x1.5 |
| Port thread 31          | NPT 1/4         | NPT 1/4         | NPT 1/4          | NPT 1/4          | NPT 1/4          | NPT 1/4          |
| Temperature range       | -40°C To +80°C  | -40°C To +80°C  | -40°C To +80°C   | -40°C To +80°C   | -40°C To +80°C   | -40°C To +80°C   |
| Port thread 11          | PT 3/8          | PT 3/8          | M14 x 1.5        | M14 x 1.5        | M14 x 1.5        | M14 x 1.5        |
| Hydraulic tank dia      | Ø 22.22 mm      | Ø 22.22 mm      | Ø 22.22 mm       | Ø 22.22 mm       | Ø 22.22 mm       | Ø 22.22 mm       |
| Air tank dia            | Ø 105 mm        | Ø 105 mm        | Ø 90 mm          | Ø 70 mm          | Ø 90 mm          | Ø 70 mm          |
| Size (L x B x H)        | 280 x 193 x 121 | 334 x 193 x 121 | 273 x 177 x 106  | 276 x 167 x 91.5 | 266 x 177 x 106  | 266 x 163 x 91.5 |
| Weight (kg)             | 3.5             | 4.1             | 2.9              | 2.4              | 2.1              | 1.7              |





## **About ProVia**

ProVia is a commercial vehicle budget spare parts brand that delivers reliable performance, with no frills, yet no compromise on quality or safety for trucks, buses, and trailers.

ProVia is available to distributors, workshops and fleet operators serving the commercial vehicle industry worldwide.


For more information, visit

www.provia-auto.com

www.wabco-customercentre.com.







#### DISCLAIMER

The data or information contained in this document are intended for authorized ProVia distributors only, and shall not be passed to any third party.

The document is provided for informative purposes only, and the provision shall not be construed as a warranty or guarantee regarding the accuracy, adequacy, completeness, timeliness or usefulness of the data or information or the characteristics of a product.

WABCO shall not be held liable for errors or omissions in the data or information, or for any damage, including, without limitation, lost profits or consequential damages, relating in any way to the use of the data and information, except in case the respective damage is based on an event caused by willful intent or gross negligence.

